Dutch Star Tag

2014 MODEL YEAR

XCR SERIES MOTORHOME





Driven By You



DRIVEN BY YOU

Freightliner Custom Chassis Corporation (FCCC) brings a rich heritage, in-depth knowledge and resources, plus a suite of quality products that delivers superior performance, safety and reliability. Located in Gaffney, South Carolina, FCCC is a company founded on hard work and family values. We are built on three founding principles — proven Brand, personal service and superior performance.

As a Daimler company, we share a culture focused on innovation and a commitment to exceed customer expectations. We are the only chassis manufacturer to offer 24/7/365 factory-direct support in order to provide our customers the best possible assistance and answers to even the most complex chassis issues. Our 24/7/365 help line can be reached at 800.FTL.HELP, or email us at fcccservice@daimler.com.

KEY POINTS

- 5-year, 100,000-mile coolant
- Synthetic transmission fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco air cleaner
- · Air filter restriction indicator
- 1,000-watt in-block engine heater
- Engine braking: 2 Stage Engine compression brake
- R-134A air conditioning compressor with condenser
- Electronic cruise control with high idle
- VIP SmartWheel, 18 in (457 mm)
- TRW column drive with adjustable tilt/telescoping steering column
- Suspended adjustable pedals
- Push button shift control
- Driver message center with integral LCD display
- Air ride suspension / Sachs tuned shock absorbers
- · Coated polished aluminum wheels with trim kit
- Bendix AD-9 heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Daytime running lights
- Tow power connector

XCR Series Dutch Star Tag	
Engine	Cummins ISL9 turbocharged aftercooled 8.9L electronic diesel, 450 HP @ 2,100 rpm
Torque	1250 lb/ft
Transmission	Allison 3000MH six-speed automatic with lock up
GVWR	
Front	252" WB- 14,600 lbs / 288" WB- 17,000 lbs
Rear	20,000 lbs
Tag	10,000 lbs
Total	44,600 lbs
GCWR Total	54,600 lbs
Wheel Base	252" & 288"
Axles	
Front	ZF Independent front axle, 252" WB- 14,600 lbs capacity / 288" WB- 17,000 lbs capacity
Rear	Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1
Tag	Ingersoll IMT F22, drop center, 10,000 lbs capacity
Brakes	
Front	Bendix 17" air disc brakes with ABS
Rear	16.5 x 7" drum style s-cam with ABS
Cooling System	1638 cubic-in, side-mounted radiator Remote-mounted water to oil Mechanical fan drive system
Electrical System	Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free
Frame	
Rail	Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25"
Rail Heights	Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25"
Fuel Tank	252" WB- 100 gallon / 288" WB- 150 gallon, dual fill, 13 gallon DEF tank
Shocks	Tuned Sachs shocks a Rolls-Royce Co.
Suspension	
Front	ZF Independent
Front Wheel Cut	252" WB- 60-degree wheel cut / 288" WB- 56-degree wheel cut
Rear	Neway ADL air suspension
Tag	Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension
Tires/Wheels	252" WB- Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels 288" WB- Michelin XZA1 315/80R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 9 wheels
Controls	Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.
Hitch	10,000 lbs

CUSTOMER SUPPORT

24/7 Factory Direct Customer Support at 1-800 FTL HELP (1-800-385-4357) *Available for New and Used Freightliner Chassis.

Basic Chassis 3 years 50,000 mi / 80,500 km with towing and roadside assistance Battery 1 year 100,000 mi / 161,000 km

Brightwork 6 months Unlimited Corrosion 6 months Unlimited Corrosion 6 months Unlimited Cross members 5 years 100,000 mi / 161,000 km

Drivetrain 3 years 50,000 mi / 80,500 km

Frame Rails 5 years 100,000 mi / 161,000 km

