Ventana Tag

2015 MODEL YEAR

XCR SERIES MOTORHOME



WHEN YOU KNOW THE DIFFERENCE[™]



Driven By You



DRIVEN BY YOU

Freightliner Custom Chassis Corporation (FCCC) brings a rich heritage, in-depth knowledge and resources, plus a suite of quality products that delivers superior performance, safety and reliability. Located in Gaffney, South Carolina, FCCC is a company founded on hard work and family values. We are built on three founding principles — proven Brand, personal service and superior performance.

As a Daimler company, we share a culture focused on innovation and a commitment to exceed customer expectations. We are the only chassis manufacturer to offer 24/7/365 factory-direct support in order to provide our customers the best possible assistance and answers to even the most complex chassis issues. Our 24/7/365 help line can be reached at 800.FTL.HELP, or email us at fcccservice@daimler.com.

KEY POINTS

- 5-year, 100,000-mile coolant
- Synthetic transmission fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco air cleaner
- · Air filter restriction indicator
- 1,000-watt in-block engine heater
- Engine braking: 2 Stage Engine compression brake
- R-134A air conditioning compressor with condenser
- Electronic cruise control with high idle
- VIP SmartWheel, 18 in (457 mm)
- Comfort Drive™ with adjustable tilt/telescoping steering column
- Floor mounted pedals
- Push button shift control
- Driver message center with integral LCD display
- Neway air ride suspension / Sachs tuned shock absorbers
- · Coated polished aluminum wheels with trim kit
- Bendix AD-9 heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Daytime running lights
- Tow power connector

Engine Cummins ISL9 turbocharged, aftercooled 8.9L electronic diesel, 400 HP @ 2,100 rpm Tronamission Allison 3000MH six-speed automatic with lock up GWWR Front 14,000 lbs Front 14,000 lbs Provided (a) (b) (b) (b) (b) (b) (b) (b) (b) (b) (b	XCR Series Ventana Tag	
Transmission Allison 3000MH six-speed automatic with tock up Front 14,000 bs Rear 20,000 lbs Total 40,000 lbs Total 44,000 lbs GCWR Total 54,000 lbs GCWR Total 54,000 lbs Wheel Base 245" & 281" Axtes Pront Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity axle ratio 4.78:1 Tag Ingersoil IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1355 cubic-munited radiator Remote-munited variet to oli oli bell-driven with viscous fan cubic to oli oli bell-driven with viscous fan cubic Batting: Danso 12 volt Batting: Danso 14 volt Batting: Danso 14 volt Batting: Danso 15 volt Batting: Dans	Engine	Cummins ISL9 turbocharged, aftercooled 8.9L electronic diesel, 400 HP @ 2,100 rpm
Front 14,000 lbs 20,000 lbs 10,000 lbs 10,00	Torque	1250 lbs/ft @ 1,400 rpm
Front 14,000 lbs Rear 20,000 lbs Total 44,000 lbs GCWR Total 54,000 lbs Wheel Base 245* & 281* Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17* air disc brakes with ABS Rear 16.5 x 7" drum style -s-cam with ABS Cooling System 13.3 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting; Denso 12 volt Battey: (2) 1600 CCA © 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Frost Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply, 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Spetch of the American Article and collabor planer, air cleaner resisted on gauge.	Transmission	Allison 3000MH six-speed automatic with lock up
Tag 10,000 lbs Tag 10,000 lbs Total 44,000 lbs GCWR Total 54,000 lbs Wheel Base 245" & 281" Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System Remover and the state of the s	GVWR	
Tag 10,000 lbs Total 44,000 lbs GCWR Total 54,000 lbs Wheel Base 245° & 281° Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity Rear Ingersoll IMT F22, drop center, 10,000 lbs capacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacity Rear Ingersoll IMT F22, drop center, 10,000 lbs. apacit	Front	14,000 lbs
Total 44,000 lbs GCWR Total 54,000 lbs Wheel Base 245" & 281" Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x.7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Raii Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rear	20,000 lbs
GCWR Total 54,000 lbs Wheel Base 245" & 281" Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belf-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Wheel Cut Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner	Tag	10,000 lbs
Wheel Base 245" & 281" Axles Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 voil Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Total	44,000 lbs
Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Bell-driven with viscous fan clutch Bell-driven with viscous fan clutch Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls \$5.edgree rimary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	GCWR Total	54,000 lbs
Front Detroit I-Beam, wide track, 14,700 lbs capacity Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Starting: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Wheel Base	245" & 281"
Rear Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1 Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leoce-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Axles	
Tag Ingersoll IMT F22, drop center, 10,000 lbs capacity Brakes Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Raii Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 5-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Front	Detroit I-Beam, wide track, 14,700 lbs capacity
Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rear	Detroit DA-RS-21.0 21,000 lbs. capacity, axle ratio 4.78:1
Front Bendix 17" air disc brakes with ABS Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Newille Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Tag	Ingersoll IMT F22, drop center, 10,000 lbs capacity
Rear 16.5 x 7" drum style s-cam with ABS Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Brakes	
Cooling System 1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Front	Bendix 17" air disc brakes with ABS
Remote-mounted water to oil Belt-driven with viscous fan clutch Electrical System Alternator: 200 amp Leece-Neville Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Frame Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rear	16.5 x 7" drum style s-cam with ABS
Starting: Denso 12 volt Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free Rail Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25" Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Cooling System	Remote-mounted water to oil
Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Electrical System	Starting: Denso 12 volt
Rail Heights Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25" Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Frame	
Fuel Tank 100 gallon, dual fill, 13 gallon driver side DEF tank Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rail	Raised frame rail with lowered rear section: 9.00" x 2.75" x 0.25"
Shocks Tuned Sachs shocks a Rolls-Royce Co. Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rail Heights	Upper-9.0" x 2.75" x .25" Lower-9.0" x 2.75" x .25"
Suspension Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Fuel Tank	100 gallon, dual fill, 13 gallon driver side DEF tank
Front Neway AS air suspension with Comfort Drive™ Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Shocks	Tuned Sachs shocks a Rolls-Royce Co.
Front Wheel Cut 55-degree wheel cut Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Suspension	
Rear Neway ADL air suspension Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Front	Neway AS air suspension with Comfort Drive™
Tag Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Front Wheel Cut	55-degree wheel cut
Tires/Wheels Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Rear	Neway ADL air suspension
Controls Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, compass/exterior temp, air cleaner restriction gauge.	Tag	Neway CA-110 Series 10,000 lbs Tag Axle Air Suspension
restriction gauge.	Tires/Wheels	Michelin XRV 305/70R 22.5 20-ply. 6 aluminum, 2 steel 22.5 x 8.25 wheels
Hitch 10,000 lbs	Controls	
	Hitch	10,000 lbs

CUSTOMER SUPPORT

24/7 Factory Direct Customer Support at 1-800 FTL HELP (1-800-385-4357) *Available for New and Used Freightliner Chassis.

Basic Chassis 3 years 50,000 mi / 80,500 km with towing and roadside assistance Battery 1 year 100,000 mi / 161,000 km

Brightwork 6 months Unlimited Corrosion 6 months Unlimited Corrosion 6 months Unlimited Cross members 5 years 100,000 mi / 161,000 km

Drivetrain 3 years 50,000 mi / 80,500 km

Frame Rails 5 years 100,000 mi / 161,000 km

