

Cross Country - XCS

2015 MODEL YEAR

XCS SERIES MOTORHOME



Driven By You



DRIVEN BY YOU

Freightliner Custom Chassis Corporation (FCCC) brings a rich heritage, in-depth knowledge and resources, plus a suite of quality products that delivers superior performance, safety and reliability. Located in Gaffney, South Carolina, FCCC is a company founded on hard work and family values. We are built on three founding principles — proven Brand, personal service and superior performance.

As a Daimler company, we share a culture focused on innovation and a commitment to exceed customer expectations. We are the only chassis manufacturer to offer 24/7/365 factory-direct support in order to provide our customers the best possible assistance and answers to even the most complex chassis issues. Our 24/7/365 help line can be reached at 800.FTL.HELP, or email us at fcccservice@daimler.com.

KEY POINTS

- 5-year, 100,000 mile coolant
- TranSynd transmission fluid
- Lowered engine
- 750-watt engine block heater
- VGT Engine brake
- Bendix AD-9 heated air dryer
- TRW tilt/telescoping steering column
- Push button shift control
- Drivers message center
- Tow power connector
- Daylight driving lights

XCS Series Cross Country - XCS

Engine	Cummins ISB 6.7L 340 HP @ 2,600 rpm
Torque	700 lbs/ft @ 1,600 rpm
Transmission	Allison 2100MH six-speed automatic with lock up
GVWR	
Front	10,500 lbs
Rear	17,500 lbs
Tag	N/A
Total	26,000 lbs
GCWR Total	30,000 lbs
Wheel Base	208"
Axles	
Front	Detroit I-Beam, wide track, 10,500 lbs capacity
Rear	Detroit DA-RS-17.5-2 17,500 lbs R-SERIES, axle ratio 4.78:1
Tag	N/A
Brakes	
Front	Full Air 15 x 4 in drum style s-cam with ABS
Rear	16.5 x 7" drum style s-cam with ABS
Cooling System	1335 cubic-in, rear-mounted radiator Remote-mounted water to oil Belt-driven with viscous fan clutch
Electrical System	160 amp Delco Remy alternator, Delco 12 volt starter, (2) 1900 CCA maintenance free batteries
Frame	
Rail	Straight frame rail with lowered rear section.
Rail Heights	9-1/8" x 2.81" x 5/16".
Fuel Tank	90 gallon, dual fill
Shocks	Tuned Sachs shocks a Rolls-Royce Co.
Suspension	
Front	Neway air suspension
Front Wheel Cut	55-degree wheel cut
Rear	Neway air suspension
Tag	N/A
Tires/Wheels	Goodyear G670 RV 255/70R 22.5 16-ply. 22.5 x 8.25 steel wheels
Controls	Speedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, air cleaner restriction gauge.
Hitch	N/A

CUSTOMER SUPPORT

24/7 Factory Direct Customer Support at 1-800 FTL HELP (1-800-385-4357) *Available for New and Used Freightliner Chassis.
 Basic Chassis 3 years 50,000 mi / 80,500 km with towing and roadside assistance
 Battery 1 year 100,000 mi / 161,000 km
 Brightwork 6 months Unlimited
 Corrosion 6 months Unlimited
 Cross members 5 years 100,000 mi / 161,000 km
 Drivetrain 3 years 50,000 mi / 80,500 km
 Frame Rails 5 years 100,000 mi / 161,000 km



INDUSTRY'S BEST WARRANTY • LARGEST SERVICE NETWORK
 Call Freightliner Custom Chassis Corporation at (800) 545-8831, or visit us on the Web at freightlinerchassis.com.

2014-06-04. Specifications are subject to change without notice. Freightliner Custom Chassis Corporation is registered to ISO 9001:2000 and ISO 14001:2004.
 © 2013 Daimler Trucks North America LLC. All rights reserved. Freightliner Custom Chassis Corporation is a subsidiary of Daimler Trucks North America LLC, a Daimler company.