

# London Aire Tag

2016 MODEL YEAR

SL SERIES MOTORHOME



WHEN YOU KNOW THE DIFFERENCE<sup>SM</sup>

Driven By You



## DRIVEN BY YOU

Freightliner Custom Chassis Corporation (FCCC) brings a rich heritage, in-depth knowledge and resources, plus a suite of quality products that delivers superior performance, safety and reliability. Located in Gaffney, South Carolina, FCCC is a company founded on hard work and family values. We are built on three founding principles — proven Brand, personal service and superior performance.

As a Daimler company, we share a culture focused on innovation and a commitment to exceed customer expectations. We are the only chassis manufacturer to offer 24/7/365 factory-direct support in order to provide our customers the best possible assistance and answers to even the most complex chassis issues. Our 24/7/365 help line can be reached at 800.FTL.HELP, or email us at [fcccservice@daimler.com](mailto:fcccservice@daimler.com).

## KEY POINTS

- 5-year, 100,000-mile coolant
- Synthetic transmission fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco air cleaner
- Air filter restriction indicator
- 1,500-watt in-block engine heater
- Engine braking: 3 Stage Engine compression brake
- R-134A air conditioning compressor with condenser
- Electronic cruise control with high idle
- VIP SmartWheel, 18 in (457 mm)
- Comfort Drive™ with adjustable tilt/telescoping steering column
- Suspended adjustable pedals
- Automatic traction control
- Self leveling system
- Optional adaptive cruise and collision warning system
- Push button shift control
- Driver message center with integral LCD display
- Air ride suspension / Sachs tuned shock absorbers
- Coated polished aluminum wheels with trim kit
- Heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Daytime running lights
- Tow power connector

## SL Series London Aire Tag

|                          |  |
|--------------------------|--|
| <b>Engine</b>            | Cummins ISX15 diesel, 600 HP @ 1,800 rpm   |
| Torque                   | 1950 lb/ft   |
| <b>Transmission</b>      | Allison 4000MH six-speed automatic with lock up  |
| <b>GVWR</b>              |  |
| Front                    | 20,000 lbs   |
| Rear                     | 20,000 lbs   |
| Tag                      | 14,000 lbs   |
| Total                    | 54,000 lbs   |
| <b>GCWR Total</b>        | 69,000 lbs   |
| <b>Wheel Base</b>        | 292"   |
| <b>Axles</b>             |  |
| Front                    | ZF independent front axle, 20,000 lbs capacity   |
| Rear                     | RC-25-160 25,000 lb R-SRS quiet ride, axle ratio 4.30:1  |
| Tag                      | Ultra Steer B-series FF, 14,000 lbs capacity   |
| <b>Brakes</b>            |  |
| Front                    | Bendix air disc brakes with ABS  |
| Rear                     | Bendix air disk brakes with ABS on drive and tag   |
| <b>Cooling System</b>    | 1680 cubic-in, side-mounted radiator<br>Mechanical fan drive system  |
| <b>Electrical System</b> | Alternator: 240 amp Leece-Neville<br>Battery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free   |
| <b>Frame</b>             |  |
| Rail                     | Raised frame rail with lowered rear section:   |
| Rail Heights             | Front-11.0" x 3.0" x .31" Upper-9.5" x 3.0" x .31" with liner Rear-10.0" x 3.0" x .31"   |
| <b>Fuel Tank</b>         | 150 gallon, dual fill, 15 gallon driver side DEF fill  |
| <b>Shocks</b>            | Tuned Sachs shocks a Rolls-Royce Co.   |
| <b>Suspension</b>        |  |
| Front                    | ZF Independent with Comfort Drive™   |
| Front Wheel Cut          | 52-degree wheel cut; Tag= 12-degree wheel cut  |
| Rear                     | V-ride air suspension  |
| Tag                      | Ultra Steer B-SRS 14,000 lbs Tag Axle Air Suspension with 12-degree wheel cut  |
| <b>Tires/Wheels</b>      | Michelin XZA 365/70R 22.5 20-ply in front, XZA1 315/80R 22.5 20-ply on drive and tag. 8 aluminum wheels  |
| <b>Controls</b>          | Speedo, tach, primary/secondary air gauge, fuel and volt gauge, trans temp, engine coolant/pressure, compass/exterior temp, air cleaner restriction ga |
| <b>Hitch</b>             | 15,000 lbs   |

## CUSTOMER SUPPORT

24/7 Factory Direct Customer Support at 1-800 FTL HELP (1-800-385-4357) \*Available for New and Used Freightliner Chassis.  
 Basic Chassis 3 years 50,000 mi / 80,500 km with towing and roadside assistance  
 Battery 1 year 100,000 mi / 161,000 km  
 Brightwork 6 months Unlimited  
 Corrosion 6 months Unlimited  
 Cross members 5 years 100,000 mi / 161,000 km  
 Drivetrain 3 years 50,000 mi / 80,500 km  
 Frame Rails 5 years 100,000 mi / 161,000 km



INDUSTRY'S BEST WARRANTY • LARGEST SERVICE NETWORK  
 Call Freightliner Custom Chassis Corporation at (800) 545-8831, or visit us on the Web at [freightlinerchassis.com](http://freightlinerchassis.com).

**2015-03-04.** Specifications are subject to change without notice. Freightliner Custom Chassis Corporation is registered to ISO 9001:2000 and ISO 14001:2004.

© 2013 Daimler Trucks North America LLC. All rights reserved. Freightliner Custom Chassis Corporation is a subsidiary of Daimler Trucks North America LLC, a Daimler company.