Marquis 380 Non-Tag - IFS

2018 MODEL YEAR

XCM SERIES MOTORHOME

Monaco RV



Driven By You





DRIVEN BY YOU

Freightliner Custom Chassis Corporation (FCCC) brings a rich heritage, in-depth knowledge and resources, plus a suite of quality products that delivers superior performance, safety and reliability. Located in Gaffney, South Carolina, FCCC is a company founded on hard work and family values. We are built on three founding principles — proven Brand, personal service and superior performance.

As a Daimler company, we share a culture focused on innovation and a commitment to exceed customer expectations. We are the only chassis manufacturer to offer 24/7/365 factory-direct support in order to provide our customers the best possible assistance and answers to even the most complex chassis issues. Our 24/7/365 help line can be reached at 800.FTL.HELP, or email us at fcccservice@daimler.com.

KEY POINTS

- OAT (Nitrate & Silicate Free) Extended Life Coolant
- Synthetic transmission fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco air cleaner
- · Air filter restriction indicator
- 1,000-watt in-block engine heater
- Engine braking: Jacobs 2-Stage Compressions Brake
- R-134A air conditioning compressor with condenser
- Electronic cruise control with high idle
- VIP SmartWheel, 18 in (457 mm) Leather wrapped
- TRW adjustable tilt/telescoping steering column
- Push button shift control
- Driver message center with integral LCD display
- V-Ride rear air ride suspension / Sachs tuned shock absorbers
- Polished aluminum wheels with trim kit
- Bendix AD-9 heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Daytime running lights
- Tow power connector
- Driver's side DEF Tank

Torque 1150 Transmission Alliso GVWR Front 14,60 Rear 24,00 Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	600 lbs 600 lbs
Transmission Alliso GVWR 14,60 Rear 24,00 Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	son 3000MH six-speed automatic with lock up torque converter 500 lbs 500 lbs 600 lbs 600 lbs 1 Independant IFS, 14,600 lbs capacity
GVWR Front 14,60 Rear 24,00 Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	600 lbs 000 lbs 600 lbs 600 lbs 600 lbs 600 lbs 11
Front 14,60 Rear 24,00 Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	000 lbs 600 lbs 600 lbs " Independant IFS, 14,600 lbs capacity
Rear 24,00 Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	000 lbs 600 lbs 600 lbs " Independant IFS, 14,600 lbs capacity
Tag N/A Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	Independant IFS, 14,600 lbs capacity
Total 38,60 GCWR Total 48,60 Wheel Base 284" Axles	600 lbs 600 lbs ." Independant IFS, 14,600 lbs capacity
GCWR Total 48,60 Wheel Base 284" Axles	Independant IFS, 14,600 lbs capacity
Wheel Base 284" Axles	Independant IFS, 14,600 lbs capacity
Axles	Independant IFS, 14,600 lbs capacity
Front ZF Inc	
	roit RS-24 axle ratio 4.78:1, 24,000 lbs capacity
Rear Detro	
Tag N/A	
Brakes	
Front Bend	ndix 22" air disc brakes with ABS
Rear Bend	ndix 22" air disc brakes with ABS
Remo	8 square-in, Side-mounted radiator note-mounted water to oil transmission Cooler t driven w/ viscous fan clutch
Startii	ernator: 160 amp Delco Remy rting: Denso 12 volt tery: (2) 1900 CCA @ 0-degrees F (-18-degrees C); maintenance free
Frame	
Rail Modu	dular frame rail with lowered rear section. 5/16"x2.75"x9" Front and Rear
Rail Heights Powe	ver Bridge center section
Fuel Tank 100 g	gallon, dual fill
Shocks Tune	ned Sachs shocks
Suspension	
Front ZF ind	independant air suspension
Front Wheel Cut 60-de	degree wheel cut
Rear V-Rid	lide air suspension
Tag N/A	
Tires/Wheels Miche	helin XZA2 Energy 295/80R 22.5 16-ply. 4 aluminum, 2 steel 22.5 x 8.25 wheels
Controls Spee	eedo, tach, primary/secondary air gauge, fuel and volt gauge, engine coolant/pressure, air cleaner restriction gauge.
Hitch 10,00	000 lb Class IV Hitch Receiver

CUSTOMER SUPPORT

24/7 Factory Direct Customer Support at 1-800 FTL HELP (1-800-385-4357) *Available for New and Used Freightliner Chassis.

Basic Chassis 3 years 50,000 mi / 80,500 km with towing and roadside assistance Battery 1 year 100,000 mi / 161,000 km

Brightwork 6 months Unlimited Corrosion 6 months Unlimited Corrosion 6 months Unlimited Cross members 5 years 100,000 mi / 161,000 km

Drivetrain 3 years 50,000 mi / 80,500 km

Frame Rails 5 years 100,000 mi / 161,000 km

