

# Coachmen Sportscoach RD

Floor plans: 404RB, 407FW, 408DB, 409BG

## 5-STAR FEATURES



24/7 factory-direct phone support  
Free mobile app: Search "Freightliner 24/7"



Increased towing capacity  
Superior roll stability & handling  
Greater durability & longevity

### ENGINE

|                   |                    |
|-------------------|--------------------|
| <b>Make</b>       | Cummins B6.7       |
| <b>Horsepower</b> | 360 HP @ 2,600 rpm |
| <b>Torque</b>     | 800 lb/ft          |

### WEIGHT RATINGS

|                   |            |
|-------------------|------------|
| <b>Front GAWR</b> | 12,000 lbs |
| <b>Rear GAWR</b>  | 20,000 lbs |
| <b>Tag GAWR</b>   | N/A        |
| <b>Total GVWR</b> | 32,000 lbs |
| <b>Total GCWR</b> | 42,000 lbs |

### TRANSMISSION

|              |                      |
|--------------|----------------------|
| <b>Type</b>  | Automatic            |
| <b>Gears</b> | Allison 3000 6-speed |

### FUEL

|                  |            |
|------------------|------------|
| <b>Type</b>      | Diesel     |
| <b>Fuel Tank</b> | 100 Gallon |
| <b>Def Tank</b>  | 13 Gallon  |

### SUSPENSION

|                  |                       |
|------------------|-----------------------|
| <b>Front</b>     | NEWAY                 |
| <b>Wheel Cut</b> | 55 Degree front wheel |
| <b>Rear</b>      | V-Ride                |

### SHOCKS

|             |                    |
|-------------|--------------------|
| <b>Make</b> | Sachs custom tuned |
|-------------|--------------------|

### AXLES

|              |                      |
|--------------|----------------------|
| <b>Front</b> | Detroit DA-F-12.0-3  |
| <b>Rear</b>  | Detroit DA-RS-20.0-4 |

### BRAKES

|              |                                 |
|--------------|---------------------------------|
| <b>Front</b> | Bendix Air Disc Brakes with ABS |
| <b>Rear</b>  | Meritor CAM Brakes with ABS     |

### RAILS

|              |                      |
|--------------|----------------------|
| <b>Front</b> | 9.0" x 2.75" x 0.25" |
| <b>Upper</b> | 9.0" x 2.75" x 0.25" |
| <b>Rear</b>  | 9.0" x 2.75" x 0.25" |

### FRAME

|                     |                                       |
|---------------------|---------------------------------------|
| <b>Construction</b> | Raised rail with lowered rear section |
| <b>Wheel Base</b>   | 266"                                  |

### COOLING

|                 |                             |
|-----------------|-----------------------------|
| <b>Radiator</b> | 1,335 sq/inch, Rear mounted |
|-----------------|-----------------------------|

### HITCH

|                 |            |
|-----------------|------------|
| <b>Capacity</b> | 10,000 lbs |
|-----------------|------------|

### TIRES

|                   |                     |
|-------------------|---------------------|
| <b>Make</b>       | Michelin XZE2       |
| <b>Front Size</b> | 275/80R 22.5 14-ply |
| <b>Rear Size</b>  | 275/80R 22.5 14-ply |
| <b>Wheels</b>     | 8.25" Aluminum      |

### ELECTRICAL

|                   |                             |
|-------------------|-----------------------------|
| <b>Alternator</b> | 160 Amp                     |
| <b>Battery</b>    | (2) 1,900 CCA @ 0 degrees F |

### CONTROLS

|                        |  |
|------------------------|--|
| <b>Steering Column</b> | TRW Tilt/3" Telescopic                   |
| <b>Steering Wheel</b>  | V.I.P. 4-SPOKE 18" (450MM) BLACK         |
| <b>Instruments</b>     | Analog gauges w/ integral message center |

### WARRANTY

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Basic Chassis / Drivetrain</b> | 3 years, 50,000 mi  |
| <b>Engine</b>                     | 5 years, 100,000 mi |
| <b>Transmission</b>               | 5 years, 200,000 mi |
| <b>Battery</b>                    | 1 year, 100,000 mi  |
| <b>Corrosion / Brightwork</b>     | 6 months unlimited  |
| <b>Frame Rails / Cross Member</b> | 5 years, 100,000 mi |