




XCR- Series Motorhome Chassis

<u>FEATURE</u>	<u>BENEFIT</u>
■ 3 Year, 50,000 Mile Warranty	Best in The Industry
■ 50,000 PSI Frame Rail	Solid Foundation
■ 55 Degree Wheel Cut	Excellent Maneuverability
■ 400 Dealers	Service Where You Need It

2008 MODEL YEAR



SEE YA'
Founders Edition
by Alfa Leisure

SEE YA' Founders Edition Custom Chassis Features

- 5 year, 100,000 mile coolant ***
- TranSynd Transmission Fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco-air cleaner
- Air filter restriction indicator
- 750 watt in-block engine heater
- Engine Braking: VGT
- R-134A air conditioning compressor with condensor
- Electronic cruise control with high idle
- VIP steering wheel, 18 in (457 mm)
- TRW infinitely adjustable tilt/telescoping steering column
- Push button shift control
- Driver message center with intergral LCD display
- Neway air ride suspension/Sachs tuned shock absorbers
- Goodyear G670 RV 255/70R 22.5 LRH tires
- Heater hose assembly to front of chassis
- Haldex PURest heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Day Time running lights
- Tow power connector

* Towing capacity limited by towing components and their attachment to the frame. See operators manual for braking requirements on towed vehicles

** Tire size may affect wheel cut.

*** Some maintenance required

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 4/05/07, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



XCR-SERIES

Engine Peak Hp Peak Torque	Cummins ISB turbocharged, aftercooled, 6.7 L electronic diesel 350 Hp @ 2,600 rpm 750 lb•ft (1017 N•m) @ 1,600 rpm
Transmission Gear Ratios:	Allison 3000MH six-speed automatic with lock up <u>First:</u> <u>Second:</u> <u>Third:</u> <u>Fourth:</u> <u>Fifth:</u> <u>Sixth:</u> <u>Rev:</u> 3.49:1 1.86:1 1.41:1 1.00:1 .75:1 .65:1 5.03:1
Vehicle Weight Ratings Front GAWR Rear GAWR GVWR GCWR *	10,500 lb (4767 kg) 19,000 lb (8626 kg) 29,500 lb (13 393 kg) 39,500 lb (17 933 kg)
Wheelbase	228 in (5791 mm) 252 in (6401 mm)
Front Axle Capacity Track Width	I-Beam, wide track 10,500 lb (4767 kg) 82.36 in (2092 mm)
Rear Axle Drive Ratio Capacity Track Width	4.78:1 19,000 lb (8626 kg) 72.1 in (1830 mm)
Brakes Front and Rear Service Parking	Full air brakes with auto slack adjusters and ABS 15 x 4 in (front) and 16.5 x 7 in (rear) drum-style S-cam Spring-applied air release 16.5 x 7 in drum-style (rear axle) Push-pull lever controlled
Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan	2 rows, 15 FPI, 1191 in ² (7685 cm ²) area Cross-flow, rear mounted Cross-flow Remote mounted water-to-oil Belt driven with viscous fan clutch
Electrical System Alternator Starting Battery	Leece-Neville 170 amp Delco 29MT, 12 volt Two 760 CCA @ 0°F (-18°C); maintenance-free
Frame Max Resist. Bending Moment Max Frame Section	Raised Frame Rail with Lowered Rear Section 291,000 lb•in (32 892 N•m) 9.00 x 2.75 x .25 in
Fuel Tank	90 gal (341 L), left fuel fill
Steering System Rating Ratio Pump Wheel Cut**	TRW THP 60, integral hydraulic power gear 12,000 lb (5448 kg) 20.4:1 Gear-driven 55°
Suspension Shock Absorber Heavy-Duty Stabilizer Bar Diam	Neway air suspension (front and rear) Tuned shocks, Sachs 1.50 in (38 mm) (front)
Tires	Goodyear G670 RV 255/70R 22.5 LRH
Wheels	Steel 22.5 x 8.25 in (572 x210mm) with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center
Instrumentation	Gauges: Speedometer • Tachometer • Engine Oil Pressure • Water Temperature • Voltmeter • Fuel Level • Dual Air Pressure