



PROVIDENCE

2013 Model Year
XCM Tag Axle-Series Motorhome Chassis

FEATURE

3-Year, 50,000-Mile Warranty
50,000 PSI Frame Rail
55-Degree Wheel Cut
400 Dealers

BENEFIT

Best in The Industry
Solid Foundation
Excellent Maneuverability
Service Where You Need It



Driven By You



Custom Chassis Features

- 5-year, 100,000-mile coolant ***
 - Synthetic transmission fluid
 - Lowered engine • 18.7 CFM air compressor
 - Fuel/water separator
 - Farr Eco air cleaner
 - Air fliter restriction indicator
 - 1 000-watt in-block engine heater
 - Engine braking: 2 Stage Engine compression brake
 - R-134A air conditioning compressor with condensor
 - Electronic cruise control with high idle
 - VIP SmartWheel, 18 in (457 mm)
 - TRW infinitely adjustable tilt/ telescoping steering column
 - Push button shift control
 - Driver message center with integral LCD display
 - Neway air ride suspension/Sachs tuned shock absorbers
 - Goodyear G670 RV 295/80
 - Polished aluminum wheels with trim kit
 - Heater hose assembly to front of chassis
 - Wabco SS-1200 hearded air dryer
 - Automatic, heated moisture ejector
 - Air suspension deflation system
 - Daytime running lights
 - Tow power connector
- * *Towing capacity limited by towing components and their attachment to the frame. See operator's manual for braking requirements on towed vehicles*
- ** *Tire size may affect wheel cut.*
- ****Some maintenance required*

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 03/29/12, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



Driven By You

XCM SERIES

Engine Peak HP Peak Torque	Cummins ISL turbocharged, aftercooled 9 L electronic diesel 450 HP @ 2,100 rpm 1250 lb•ft (1424 Nom) @ 1,400 rpm
Transmission Gear Ratios	Allison 3000 MH six-speed automatic with lock up First Second Third Fourth Fifth Sixth Rev. 3.49:1 1.86:1 1.41:1 1.00:1 .75:1 .65:1 5.03:1
Vehicle Weight Ratings Front GAWR Rear GAWR GVWR GCWR *	14,700 lbs. 20,000 lbs. Tag: 10,000 lbs. 44,700 lbs. 54,700 lbs.
Wheelbase	278 in
Front Axle Capacity Track Width	I-Beam, wide track 14,700 lbs. 82.89 in (2105 mm)
Rear Axle Drive Ratio Capacity Track Width	4.88:1 20,000 lb (9080 kg) 72.1 in (1830 mm)
Brakes Front Service Rear Service Parking	Full air brakes with auto slack adjusters and ABS Front disc brake 16.5 x 7 in drum-style s-cam Tag: 15x4 drum-style s-cam 16.5 x 7 in drum-style s-cam Spring-applied air release
Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan	2 rows, 15 FPI, 1638 in2 Cross-flow, side-mounted Cross-flow, side-mounted Remote-mounted water to oil Belt-driven with viscous fan clutch
Electrical System Alternator Starting Battery	Leece-Neville 170 amp Denso 12 volt Two 1900 CCA @ 0°F (-18°C); maintenance-free
Frame Max Resist. Bending Moment Max Frame Section	Modular frame rail with lowered rear Section 495,800 lboin (56 010 Nom) 9.00 x 2.75 x 5/16 in
Fuel Tank	150 gal (578 L), dual fuel fill
Steering System Rating Ratio Pump Wheel Cut **	TRW THP 86, integral hydraulic power gear 14,700 lbs. 20.4:1 Gear-driven 55°
Suspension Shock Absorber Heavy-duty Stabilizer Bar Diam	Neway air suspension (front and rear) Tuned shocks, Sachs 1.50 in (38 mm) (front)
Tires	Goodyear G670 RV 295/80
Wheels	4 aluminum 2 steel 22.5 x 8.25 in (572x210mm) with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center
Instrumentation	Gauges: speedometer • tachometer • engine oil pressure • water temperature • voltmeter • fuel level • dual air pressure