




XCR- Series Motorhome Chassis

<u>FEATURE</u>	<u>BENEFIT</u>
■ 3 Year, 50,000 Mile Warranty	Best in The Industry
■ 50,000 PSI Frame Rail	Solid Foundation
■ 60 Degree Wheel Cut	Excellent Maneuverability
■ 400 Dealers	Service Where You Need It

2007 MODEL YEAR



Tsunami
by Forest River

Tsunami by Forest River Custom Chassis Features

- 5 year, 100,000 mile coolant ***
- TranSynd Transmission Fluid
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco-air cleaner
- Air filter restriction indicator
- 1000 watt in-block engine heater
- C brake w/Hi Lo Switch
- R-134A air conditioning compressor and condensor
- Electronic cruise control with high idle
- VIP *Smart Wheel*, 18 in (457mm)
- TRW infinitely adjustable tilt/telescoping steering column
- Suspended and adjustable pedals
- Push button shift control
- Driver message center with intergral LCD display
- ZF- IFS (front) Neway ADL (rear) air ride suspension/Custom tuned Sachs shock absorbers
- Michelin XZA1 295/80RX22.5, LRH tires
- Polished aluminum wheels with trim kit
- Heater hose assembly to front of chassis
- Haldex PUrest heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Day time running lights
- Tow power connector

* Towing capacity limited by towing components and their attachment to the frame. See operators manual for braking requirements on towed vehicles

*** Some maintenance required

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 8/04/06, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



XCR-SERIES

Engine Peak Hp Peak Torque	Cummins ISL turbocharged, aftercooled, 8.9 L electronic diesel 400 Hp @ 2,200 rpm 1200 lb•ft (1627 N•m) @ 1,300 rpm
Transmission Gear Ratios	Allison 3000MH six-speed automatic with lock up <u>First</u> <u>Second</u> <u>Third</u> <u>Fourth</u> <u>Fifth</u> <u>Sixth</u> <u>Rev.</u> 3.49:1 1.86:1 1.41:1 1.00:1 .75:1 .65:1 5.03:1
Vehicle Weight Ratings Front GAWR Rear GAWR GVWR GCWR *	14,600 lb (6629 kg) 20,000 lb (9080 kg) 34,600 lb (15 708 kg) 49,600 lb (22 518 kg)
Wheelbase	252 in 276 in (6401mm) (7010mm)
Front Axle Capacity Track Width	ZF - RL67EM Independent Front Suspension 14,600 lb (6629 kg) 84.3 in (2141 mm)
Rear Axle Drive Ratio Capacity Track Width	Meritor RS-19-144 4.63:1 20,000 lb (9080 kg) 72.1 in (1830 mm)
Brakes Front Service Rear Service Parking	Full air brakes with ABS 17 in Disc rotors with wear sensors 16.5x7 in drum-style S-camwith auto slack adjusters Spring-applied, air release 16.5x7 in drum-style (rear axle) Push-pull lever controlled
Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan	2 rows, 14 FPI 1,000 in ² (6452 cm ²) area Cross-flow, side mounted Cross-flow, side mounted Remote mounted water-to-oil Variable speed, hydraulic
Electrical System Alternator Starting Battery	Leece-Neville 200 amp Delco 12 volt , 41-MT Two 950 CCA @ 0°F (-18°C); maintenance-free
Frame Max Resist. Bending Moment Max Frame Section	Raised Frame Rail Construction 291,000 lb•in (32 892 N•m) 9.00 x 2.75 x .25 in (229 x 70 x 6.4 mm)
Fuel Tank	150 gal (568 L), dual fuel fill
Steering System Rating Variable Ratio Pump Wheel Cut	ZF - 8018, integral hydraulic power gear 14,600 lb (6629 kg) 19.3:1 to 22.7:1 Gear-driven 60°
Suspension Shock Absorber	ZF - RL67EM IFS air (front) Neway ADL air (rear) Custom Tuned Sachs
Tires	Michelin XZA1 295/80R 22.5, LRH
Wheels	4 aluminum, 2 steel, 22.5x 8.25 in (572x210 mm) with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center
Instrumentation	Gauges: Speedometer • Tachometer • Engine Oil Pressure • Water Temperature • Voltmeter • Fuel Level • Dual Air Pressure • Transmission Temp • Turb Boost