



ALLEGRO
OPEN ROAD™

RED

2010 Model Year

XCR-Series Motorhome Chassis

FEATURE

3-Year, 50,000-Mile Warranty
50,000 PSI Frame Rail
55-Degree Wheel Cut
400 Dealers

BENEFIT

Best in The Industry
Solid Foundation
Excellent Maneuverability
Service Where You Need It



Driven By You



Custom Chassis Features

- 5-year, 100,000-mile coolant***
- TranSynd transmission fluid
- Lowered engine
- 18.7 CFM air compressor
- Fuel/water separator
- Farr Eco air cleaner
- Air filter restriction indicator
- 750-watt in block heater
- Engine braking : VGT
- R-134A air conditioning compressor
- Electronic cruise control with high idle
- VIP steering wheel, 18 in (457 mm)
- TRW infinitely adjustable tilt/telescoping steering column
- Push button shift control
- Driver message center with integral LCD display
- 5" gauge package
- Neway air ride suspension/Sachs tuned shock absorbers
- Michelin XZE 275/80R 22.5 LRG
- Heater hose assembly to front of chassis
- Bendix AD-9 heated air dryer
- Automatic, heated moisture ejector
- Air suspension deflation system
- Daytime running lights
- Tow power connector

* Transmission limited GCWR. See operator's manual for braking requirements on towed vehicle.

***Some maintenance required

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 11/01/09, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



Driven By You

XCR SERIES

Engine Peak HP Peak Torque	Cummins ISB turbocharged, aftercooled, 6.7 L electronic diesel 340 HP @ 2,600 rpm 660 lb•ft (895 N•m) @ 1,600 rpm
Transmission Gear Ratios	Allison 2500 MH six-speed automatic with lock up First: Second: Third: Fourth: Fifth: Sixth: Rev: 3.51:1 1.90:1 1.44:1 1.00:1 .74:1 .64:1 5.09:1
Vehicle Weight Ratings Front GAWR Rear GAWR GVWR * GCWR *	12,000 lb (5448 kg) 17,500 lb (7945 kg) 29,500 lb (13,393 kg) 33,000 lb (14,982 kg)
Wheelbase	228 in (5791 mm) 252 in (6400 mm)
Front Axle Capacity Track Width	I-Beam, wide track 12,000 lb (5448 kg) 82.24 in (2089 mm)
Rear Axle Drive Ratio Capacity Track Width	4.63:1 17,500 lb (7945 kg) 69.3 in (1760 mm)
Brakes Front Service Rear Service Parking	Full air brakes with auto slack adjusters and ABS 17 in disc brakes 16.5 x 7 in drum-style s-cam 16.5 x 7 in drum-style s-cam Spring applied air release
Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan	2 rows, 15 FPI, 1191 in ² (7684 cm ²) area Cross-flow, rear-mounted Cross-flow, rear-mounted Remote-mounted water-to-oil Belt-driven with viscous fan clutch
Electrical System Alternator Starting Battery	Delco Remy 160 amp 29MT, 12 volt Two 950 CCA @ 0°F (-18°C); maintenance-free
Frame Max Resist. Bending Moment Max Frame Section	Raised frame rail with lowered rear section 406,200 lb•in (45 900 N•m) 9.00 x 2.75 x .25 in (229 x 70 x 6.4 mm)
Fuel Tank	100 gal (378 L), dual fuel fill
Steering System Rating Ratio Pump Wheel Cut	TRW THP 60, integral hydraulic power gear 12,000 lb (5448 kg) 20.4:1 Gear-driven 55°
Suspension Shock Absorber Heavy-duty Stabilizer Bar Diam	Neway air suspension Tuned shocks, Sachs 1.50 in (38 mm) (front)
Tires	Michelin XZE 275/80R 22.5 LRG
Wheels	4 Aluminum 2 Steel 22.5 x 8.25 in (572 x 210 mm) with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center
Instrumentation	Gauges: speedometer • tachometer • engine oil pressure • water temperature • voltmeter • fuel level • dual air pressure