



Adventurer

2010 Model Year

MC-Series Motorhome Chassis

FEATURE

3-Year, 50,000-Mile Warranty
50,000 PSI Frame Rail
55-Degree Wheel Cut
400 Dealers

BENEFIT

Best in The Industry
Solid Foundation
Excellent Maneuverability
Service Where You Need It



Driven By You



Adventurer

Custom Chassis Features

- 5-year 100,000-mile coolant***
- TranSynd transmission fluid
- Fuel/water separator
- Farr Eco air cleaner
- Air filter restriction indicator
- 750-watt in-block engine heater
- Engine braking : VGT
- R-134A air conditioning compressor
- Electronic cruise control with high idle
- VIP steering wheel, 18 in (457mm)
- TRW tilt steering column
- Push button shift control with park
- Driver information center
- Hendrickson suspension, Sachs tuned shock absorbers
- Michelin XRV 235/80R 22.5 LRG
- Goodyear 255/70R 22.5 G670 LRH
- Heater hose assembly
- Daytime running light

* Transmission limited GCWR. See operator,s manual for braking requirements on towed vehicle.

*** Some maintenance required

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 11/01/09, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



Driven By You

MC SERIES

| | |
|--|---|
| Engine Peak HP Peak Torque | Cummins ISB turbocharged, aftercooled 6.7 L electronic diesel 300 HP @ 2,600 rpm 620 lb•ft (841 N•m) @ 1,600 rpm |
| Transmission Gear Ratios | Allison 1000 & 2350 MH six speed automatic First: Second: Third: Fourth: Fifth: Sixth: Rev: 3.10:1 1.81:1 1.41:1 1.00:1 .71:1 .61:1 4.49:1 |
| Vehicle Weight Ratings Front GAWR Rear GAWR GVWR * GCWR * | 9,000 lb (4091 kg) / 10,000 lb (4545 kg) 15,000 lb (6818 kg) / 17,500 lb (7955 kg) 22,000 lb (10,000 kg) / 27,000 lb (12,273 kg) 26,000 lb (11,818 kg) / 30,000 lb (13,636 kg) |
| Wheelbase | 220 in (5588 mm), 228 (5791 mm), 248 (6299 mm) |
| Front Axle Capacity Track Width | Hendrickson STEERTEK I-Beam, wide track 10,000 lb (4540 kg) 79.7 in (2024 mm) |
| Rear Axle Drive Ratio Capacity Track Width | 4.78:1 15,000 lb (6818 kg) / 17,500 lb (7955 kg) 69.3 in (1760 mm) |
| Brakes Front and Rear Service Parking | Bosch hydraulic pin slide disc with ABS 15 in Drum Transmission-mounted disc Shift selector with park |
| Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan | 14 FPI, 750 in ² (4839 cm ²) area Down-flow, front-mounted Cross-flow Water-to-oil Belt-driven with viscous clutch |
| Electrical System Alternator Starting Battery | Delco Remy 160 amp Delco 29MT, 12 volt Two 650 CCA @ 0°F (-18°C); maintenance-free |
| Frame Max Resist. Bending Moment Max Frame Section | Straight frame rail construction 536,800 lb•in (60 650 N•m) 9 1/8 x 3.00 x 5/16 in (232 x 76 x 7.9 mm) |
| Fuel Tank | 80 gal (303 L), rear fuel fill |
| Steering System Rating Ratio Pump Wheel Cut | TRW THP 60, integral hydraulic power gear 10,000 lb (4540 kg) 18.2:1 Gear-driven 55° |
| Suspension Shock Absorber Heavy-Duty Stabilizer Bar Diam | Hendrickson SOFTEK (front) taperleaf (rear) Tuned Sachs shocks 1.50 in (38 mm) front 1.75 (44 mm) rear |
| Tires | Mich XRV 235/80R 22.5 , GY 255/70RG670 22.5 |
| Wheels | 4 aluminum 2 steel 22.5 x 7.5 in or 8.25 in with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center |
| Instrumentation | Gauges: speedometer • tachometer • engine oil pressure • water temperature • voltmeter • fuel level |