

Fleetwood Pace Arrow

Floor plans: 33D

5-STAR FEATURES



24/7 factory-direct phone support

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ULTRASTEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

V-RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins B6.7
Horsepower	300 HP @ 2,600 rpm
Torque	660 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	10,500 lbs
Rear GAWR	17,500 lbs
Tag GAWR	N/A
Total GVWR	26,000 lbs
Total GCWR	30,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 2100 6-speed

FUEL

Type	Diesel
Fuel Tank	90 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	NEWAY AS120
Wheel Cut	55 Degree front wheel
Rear	FCCC V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-10.5-3
Rear	Detroit DA-RS-17.5-2

BRAKES

Front	Meritor Air Drum Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

RAILS

Straight	9.125" x 2.81" x 0.3125"
-----------------	--------------------------

FRAME

Construction	Straight rail with lowered rear section
Wheel Base	208"

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

HITCH

Rating	10,000 lbs
---------------	------------

TIRES

Make	Michelin XZE
Front Size	255/70R 22.5 16-ply
Rear Size	255/70R 22.5 16-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	TRW Tilt/3" Telescopic
Steering Wheel	DriveTech steering wheel w/ OptiView controls
Instruments	OptiView LCD display, Daytime Running Lights
Safety	Featuring Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 Years / 100,000 mi.
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi