

Tiffin Phaeton

Floor plans: , 37BH, 40AH, 40QBH, 40QKH

5-STAR FEATURES



Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	380 HP @ 2,000 rpm
Torque	1,150 lb/ft

WEIGHT RATINGS

Front GAWR	14,320 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	38,320 lbs
Total GCWR	48,320 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	NEWAY AS140
Wheel Cut	55 Degree front wheel
Rear	FCCC V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix

RAILS

Front	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Modular rail with lowered rear section
Wheel Base	266"

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

HITCH

Capacity	Supplied by OEM
-----------------	-----------------

TIRES

Make	Michelin X
Front Size	275/80R 22.5 16-ply
Rear Size	275/80R 22.5 16-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp Delco Remy
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	TRW Tilt/3" Telescopic
Steering Wheel	V.I.P. SMRT 4-SPK 18"(450MM)BLK STRG WHL
Instruments	Analog gauges w/ integral message center

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi