



2021 SPEC SHEET

# Newmar New Aire

Floor plans: 3341, 3343

## 5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel  
Prioritizes driver safety



Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers



Increased towing capacity  
Superior roll stability & handling  
Greater durability & longevity

### ENGINE

<b>Make</b>	Cummins B6.7
<b>Horsepower</b>	360 HP @ 2,600 rpm
<b>Torque</b>	800 lb/ft
<b>Brake</b>	VGT (Variable Geometry Turbocharger) Brake (single stage)

### WEIGHT RATINGS

<b>Front GAWR</b>	14,600 lbs
<b>Rear GAWR</b>	24,000 lbs
<b>Tag GAWR</b>	N/A
<b>Total GVWR</b>	38,600 lbs
<b>Total GCWR</b>	48,600 lbs

### TRANSMISSION

<b>Type</b>	Automatic
<b>Gears</b>	Allison 3000 6-speed

### FUEL

<b>Type</b>	Diesel
<b>Fuel Tank</b>	90 Gallon
<b>Def Tank</b>	15 Gallon

### SUSPENSION

<b>Front</b>	ZF
<b>Wheel Cut</b>	60 Degree front wheel
<b>Rear</b>	V-Ride

### SHOCKS

<b>Make</b>	Sachs custom tuned
-------------	--------------------

### AXLES

<b>Front</b>	ZF
<b>Rear</b>	Detroit DA-RS-23.0-4

### BRAKES

<b>Front</b>	Bendix Air Disc Brakes with ABS
<b>Rear</b>	Bendix Air Drum Brakes with ABS

### RAILS

<b>Straight</b>	9.125" x 2.81" x 0.3125"
-----------------	--------------------------

### FRAME

<b>Construction</b>	Straight rail with lowered rear section
<b>Wheel Base</b>	206"

### COOLING

<b>Radiator</b>	1,234 sq/inch, Side mounted
-----------------	-----------------------------

### HITCH

<b>Rating</b>	10,000 lbs
---------------	------------

### TIRES

<b>Make</b>	Michelin XRV
<b>Front Size</b>	305/70R 22.5 20-ply
<b>Rear Size</b>	305/70R 22.5 20-ply
<b>Wheels</b>	9" Aluminum

### ELECTRICAL

<b>Alternator</b>	240 Amp Leece-Neville
<b>Battery</b>	(2) 1,900 CCA @ 0 degrees F

### CONTROLS

<b>Steering Column</b>	Column Drive with Tilt/Telescopic
<b>Steering Wheel</b>	DriveTech steering wheel with OptiView controls
<b>Instruments</b>	OptiView LCD with Roadwatch. Push Button Start and Tire Pressure Monitoring System
<b>Safety</b>	RoadWatch featuring Collision Mitigation (forward warning and active braking), Adaptive Cruise Control (ACC), Electronic Stability Control (ESC) with Roll Stability Control (RSC), Automatic Traction Control (ATC)

### WARRANTY

<b>Basic Chassis / Drivetrain</b>	3 years, 50,000 mi
<b>Engine</b>	5 years, 100,000 mi
<b>Transmission</b>	5 years, 200,000 mi
<b>Battery</b>	1 year, 100,000 mi
<b>Corrosion / Brightwork</b>	6 months unlimited
<b>Frame Rails / Cross Member</b>	5 years, 100,000 mi