

# THOR Motor Coach Tuscany Tag

Floor plans: 45JA, 45MX

## 5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel  
Prioritizes driver safety



Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan



Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

### ENGINE

<b>Make</b>	Cummins L9
<b>Horsepower</b>	450 HP @ 2,100 rpm
<b>Torque</b>	1,250 lb/ft
<b>Brake</b>	Engine Compression Brake (three stage)

### WEIGHT RATINGS

<b>Front GAWR</b>	16,000 lbs
<b>Rear GAWR</b>	20,000 lbs
<b>Tag GAWR</b>	10,000 lbs
<b>Total GVWR</b>	46,000 lbs
<b>Total GCWR</b>	61,000 lbs

### TRANSMISSION

<b>Type</b>	Automatic
<b>Gears</b>	Allison 3000 6-speed

### FUEL

<b>Type</b>	Diesel
<b>Fuel Tank</b>	150 Gallon
<b>Def Tank</b>	15 Gallon

### SUSPENSION

<b>Front</b>	ZF
<b>Wheel Cut</b>	56 Degree front wheel
<b>Rear</b>	V-Ride
<b>Tag</b>	Ultra Steer

### SHOCKS

<b>Make</b>	Sachs custom tuned
-------------	--------------------

### AXLES

<b>Front</b>	ZF
<b>Rear</b>	Detroit DA-RS-21.0-4
<b>Tag</b>	UltraSteer

### BRAKES

<b>Front</b>	Bendix Air Disc Brakes with ABS
<b>Rear</b>	Meritor CAM Brakes with ABS

### RAILS

<b>Front</b>	9.0" x 2.75" x 0.25"
<b>Upper</b>	9.0" x 2.75" x 0.25"
<b>Rear</b>	9.0" x 2.75" x 0.25"

### FRAME

<b>Construction</b>	Raised rail with lowered rear section
<b>Wheel Base</b>	287"

### COOLING

<b>Radiator</b>	1,638 sq/inch, Side mounted
-----------------	-----------------------------

### HITCH

<b>Rating</b>	15,000 lbs
---------------	------------

### TIRES

<b>Make</b>	Michelin X Line Energy Z
<b>Front Size</b>	315/80R 22.5 20-ply
<b>Rear Size</b>	295/80R 22.5 16-ply
<b>Tag Size</b>	295/80R 22.5 16-ply
<b>Wheels</b>	8.25" Aluminum

### ELECTRICAL

<b>Alternator</b>	160 Amp
<b>Battery</b>	(2) 1,900 CCA @ 0 degrees F

### CONTROLS

<b>Steering Column</b>	ZF Tilt/Telescoping with Foot Pedal
<b>Steering Wheel</b>	DriveTech steering wheel with dash controls
<b>Instruments</b>	OptiView LCD display, Daytime Running Lights, Push Button Start, Adjustable Suspended Brake and Accelerator Pedals, and TPMS

### WARRANTY

<b>Basic Chassis / Drivetrain</b>	3 years, 50,000 mi
<b>Engine</b>	5 years, 100,000 mi
<b>Transmission</b>	5 years, 200,000 mi
<b>Battery</b>	1 year, 100,000 mi
<b>Corrosion / Brightwork</b>	6 months unlimited
<b>Frame Rails / Cross Member</b>	5 years, 100,000 mi