



2022 SPEC SHEET

Holiday Rambler Nautica

Floor plans: 35MS, 35QZ

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins B6.7
Horsepower	340 HP @ 2,600 rpm
Torque	700 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	12,400 lbs
Rear GAWR	20,000 lbs
Tag GAWR	N/A
Total GVWR	32,400 lbs
Total GCWR	33,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 2500 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	NEWAY AS120
Wheel Cut	55 Degree front wheel
Rear	FCCC V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-12.4-3
Rear	Detroit DA-RS-20.0-4

BRAKES

Front	Meritor Air Drum Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

RAILS

Raised	9.0" x 2.75" x 0.25"
---------------	----------------------

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	242"

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

HITCH

Rating	10,000 lbs
---------------	------------

TIRES

Make	Michelin X Line Energy Z
Front Size	275/80R 22.5 16-ply
Rear Size	275/80R 22.5 16-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Adjustable Tilt and Telescoping
Steering Wheel	DriveTech steering wheel w/ OptiView controls
Instruments	OptiView LCD display, Daytime Running Lights

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 Years / 100,000 mi.
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi