



2022 SPEC SHEET

American Coach Tradition

Floor plans: 42V, 42Q

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety

ROADWATCH

Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers

ULTRA STEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	450 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	17,000 lbs
Rear GAWR	20,000 lbs
Tag GAWR	10,000 lbs
Total GVWR	47,000 lbs
Total GCWR	62,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	150 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	ZF IFS
Wheel Cut	56 Degree front wheel
Rear	FCCC V-Ride
Tag	FCCC UltraSteer

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	ZF
Rear	Detroit DA-RS-21.0-4
Tag	FCCC UltraSteer

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Drum Brakes with ABS

RAILS

Front	14.1875" x 2.75" x 0.25"
Rear	12.9375" x 3.0" x 0.25"

FRAME

Construction XCM Modular and lowered rear section with Liberty Foundation

Wheel Base 278"

COOLING

Radiator 1,638 sq/inch, Side mounted

HITCH

Rating 15,000 lbs

TIRES

Make	Michelin XZA2 Energy
Front Size	315/80R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Tag Size	315/80R 22.5 20-ply
Wheels	9" Aluminum w/ Tire Pressure Monitoring System

ELECTRICAL

Alternator	170 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column TRW Column Drive (Select Drive Steering Effort) w/ Tilt and Telescopic Adjust

Steering Wheel DriveTech steering wheel w/ OptiView controls

Instruments OptiView LCD Instrumentation, Daytime Running Lights, Push Button Start, Adjustable Suspended Pedals, Select Drive-Steering Effort

Safety Featuring Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 Years / 100,000 mi.
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi