

Winnebago Inspire

Floor plans: 34AE

5-STAR FEATURES



24/7 factory-direct phone support

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

V-RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

| | |
|-------------------|---|
| Make | Cummins B6.7 |
| Horsepower | 340 HP @ 2,600 rpm |
| Torque | 700 lb/ft |
| Brake | VGT (Variable Geometry Turbocharger) Brake (single stage) |

WEIGHT RATINGS

| | |
|-------------------|------------|
| Front GAWR | 10,410 lbs |
| Rear GAWR | 17,500 lbs |
| Tag GAWR | N/A |
| Total GVWR | 26,000 lbs |
| Total GCWR | 33,000 lbs |

TRANSMISSION

| | |
|--------------|----------------------|
| Type | Automatic |
| Gears | Allison 2500 6-speed |

FUEL

| | |
|------------------|-----------|
| Type | Diesel |
| Fuel Tank | 90 Gallon |
| Def Tank | 13 Gallon |

SUSPENSION

| | |
|------------------|-----------------------|
| Front | NEWAY AS120 |
| Wheel Cut | 55 Degree front wheel |
| Rear | FCCC V-Ride |

SHOCKS

| | |
|-------------|--------------------|
| Make | Sachs custom tuned |
|-------------|--------------------|

AXLES

| | |
|--------------|----------------------|
| Front | Detroit DA-F-10.5-3 |
| Rear | Detroit DA-RS-17.5-2 |

BRAKES

| | |
|--------------|-----------------------------|
| Front | Meritor CAM Brakes with ABS |
| Rear | Meritor CAM Brakes with ABS |

RAILS

| | |
|-----------------|--------------------------|
| Straight | 9.125" x 2.81" x 0.3125" |
|-----------------|--------------------------|

FRAME

| | |
|---------------------|---|
| Construction | Straight rail with lowered rear section |
| Wheel Base | 208" |

COOLING

| | |
|-----------------|-----------------------------|
| Radiator | 1,335 sq/inch, Rear mounted |
|-----------------|-----------------------------|

HITCH

| | |
|---------------|-----------------|
| Rating | Supplied by OEM |
|---------------|-----------------|

TIRES

| | |
|-------------------|---------------------|
| Make | Michelin XRV |
| Front Size | 255/80R 22.5 14-ply |
| Rear Size | 255/80R 22.5 14-ply |
| Wheels | 8.25" Aluminum |

ELECTRICAL

| | |
|-------------------|-----------------------------|
| Alternator | 160 Amp Delco Remy |
| Battery | (2) 1,900 CCA @ 0 degrees F |

CONTROLS

| | |
|------------------------|---|
| Steering Column | ZF Tilt/Telescoping with Foot Pedal |
| Steering Wheel | DriveTech steering wheel w/ OptiView controls |
| Instruments | OptiView LCD display |

WARRANTY

| | |
|-----------------------------------|---------------------|
| Basic Chassis / Drivetrain | 3 years, 50,000 mi |
| Engine | 5 years, 100,000 mi |
| Transmission | 5 years, 200,000 mi |
| Battery | 1 year, 100,000 mi |
| Corrosion / Brightwork | 6 months unlimited |
| Frame Rails / Cross Member | 5 years, 100,000 mi |